

AMD EPYC™ 7003 SERIES PROCESSORS

THE NEW STANDARD FOR THE MODERN DATA CENTER

AT A GLANCE

AMD is raising the bar once more for workload performance. Our 3rd Gen AMD EPYC™ Processors are designed to help IT professionals drive faster time to results and deliver better business outcomes. Continued enhancements to the innovative EPYC system-on-chip (SoC) design raise the bar again for performance, security features, and TCO.



WORKLOAD PERFORMANCE

Turn raw data into actionable insights faster

On premises, in the cloud, in containers, virtual machines, or on bare metal, 3rd Gen AMD EPYC 7003 Series CPUs are the market's best performing x86 server processor, helping provide faster time to results.



LEADERSHIP ARCHITECTURE

Steady multiyear execution delivers continuing innovation and technology

Based on AMD Infinity Architecture, our new 3rd Gen AMD EPYC processors deliver a full feature set across the entire CPU stack. You chose the core count and frequency; memory capabilities, advanced security features, and I/O capacity are all included at no additional cost. Our no-compromise single socket options provide exceptional performance with up to 64 cores, 128 lanes of PCIe® Gen4 connectivity, up to 4 TB of memory across 16 DIMM slots, Plus, now with up to 32MB L3 cache per core and near line rate data transmission with synchronized clocks between the AMD Infinity Fabric™ and memory, helping increase data analytic speeds.



SECURITY BY DESIGN

A modern multi-faceted approach to data center security

With advanced security features and a silicon-embedded security subsystem, 3rd Gen AMD EPYC Processors are 'hardened at the core,' helping you guard your most important assets—your data. AMD Infinity Guard² helps secure the boot process, encrypt the entire main memory with secure memory encryption (SME), and secure virtualized environments and containers with secure encrypted virtualization (SEV). Now with new AMD Shadow Stack and Secure Nested Paging (SEV-SNP) features, 3rd Gen EPYC processor security is stronger than ever. Our processors can help cryptographically isolate and secure more than 500 virtual machines per server.



DATA YOUR WAY, ON-PREMISES OR IN THE CLOUD

Gain fast time to value while maximizing IT investments

AMD EPYC CPUs deliver. No matter how you want it, when you want it, or where the data is. You get the high performance, low TCO, and outstanding time-to-value IT professionals have come to expect from AMD EPYC powered servers. Today's data centers can be and are anywhere and everywhere. This is why AMD EPYC processor-powered servers are available for your data center and in the cloud with offerings from the major server and cloud providers.

Continue reading for more technical detail



AMD EPYC™ 7003 SERIES PROCESSORS

| MODEL | CORES | THREADS | BASE FREQ. (GHZ) | UP TO MAX. BOOST FREQ. (GHZ) ³ | TDP (W) | L3 CACHE (MB) | DDR CHANNELS | UP TO MAX DDR FREQ. (1DPC) | PER-SOCKET THEORETICAL MEMORY BANDWIDTH (GB/S) | PCIE® GEN 4 LANES | 2P/1P |
|-------|-------|---------|---------------------|--|------------|------------------|-----------------|-------------------------------------|--|-------------------------|-------|
| 7763 | 64 | 128 | 2.45 | 3.50 | 280 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7713 | 64 | 128 | 2.00 | 3.675 | 225 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7713P | | | | | | | | | | | 1P |
| 7663 | 56 | 112 | 2.00 | 3.50 | 240 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7643 | 48 | 96 | 2.30 | 3.60 | 225 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7543 | 32 | 64 | 2.80 | 3.70 | 225 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7543P | | | | | | | | | | | 1P |
| 7513 | 32 | 64 | 2.60 | 3.65 | 200 | 128 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7453 | 28 | 56 | 2.75 | 3.45 | 225 | 64 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7443 | 24 | 48 | 2.85 | 4.00 | 200 | 128 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7443P | | | | | | | | | | | 1P |
| 7413 | 24 | 48 | 2.65 | 3.60 | 180 | 128 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7343 | 16 | 32 | 3.20 | 3.90 | 190 | 128 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7313 | 16 | 32 | 3.00 | 3.70 | 155 | 128 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 7313P | | | | | | | | | | | 1P |
| 75F3 | 32 | 64 | 2.95 | 4.00 | 280 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 74F3 | 24 | 48 | 3.20 | 4.00 | 240 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 73F3 | 16 | 32 | 3.50 | 4.00 | 240 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |
| 72F3 | 8 | 16 | 3.70 | 4.10 | 180 | 256 | 8 | 3200 | 204.8 | 128 | 2P/1P |

a. Maximum boost for AMD EPYC processors is the maximum frequency achievable by any single core on the processor under normal operating conditions for server systems. EPYC-18.

FOOTNOTES

- **1.** EPYC 7763. See https://www.amd.com/en/claims/epyc#faq-MLN-016.
- 2. AMD Infinity Guard features vary by EPYC processor generations. Infinity Guard features must be enabled by server OEMs and/or Cloud Service Providers to operate. Check with your OEM or provider to confirm support of these features. Learn more about Infinity Guard at https://www.amd.com/en/technologies/infinity-guard. GD-177

© 2021 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, EPYC, Infinity Fabric, and combinations thereof are trademarks of Advanced Micro Devices, Inc. in the United States and/or other jurisdictions. PCIe® is a registered trademark of PCI-SIG Corporation. Other names are for informational purposes only and may be trademarks of their respective owners. LE-77202-00 02/21